

Dependent Resurvey, Portion of E. Bdy., T. 31 S., R. 7 W.

CHAINS

- 62.15 Spur, slopes N. 45° W.; desc. 60 ft. over broken NW. slope.
- 62.80 Creek, 1 lk. wide, course N. 70° W.; asc. 180 ft. over broken SW. slope.
- 81.54 Point for the cor. of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S
R 7 W | R 6 W
S 12 | S 7
S 13 | S 18
1969

from which

- A fir, 7 ins. diam., bears N. 5° E., 68 lks. dist., mkd. T31S R6W S7 BT.
- A fir, 17 ins. diam., bears S. 12½° E., 148 lks. dist., mkd. T31S R6W S18 BT.
- A fir, 42 ins. diam., bears S. 32° W., 28 lks. dist., mkd. T31S R7W S13 BT.
- A fir, 8 ins. diam., bears N. 36½° W., 60½ lks. dist., mkd. T31S R7W S12 BT.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, cedar, hemlock, alder, and pine; undergrowth, salal, Oregon grape, fern, hazel, poison oak, and vine maple.

N. 0° 29' E., bet. secs. 7 and 12.

Descend 50 ft. over NW. slope, through moderate timber and undergrowth.

- 2.65 The cor. of secs. 7, 12, 13, and 18, established in 1855 by Wells Lake and George W. Hyde and subsequently superseeded by the William H. Byars survey in 1882, perpetuated and recorded by the Douglas County Surveyor in 1967, now becomes an angle point, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

R T 31 S R
7 S 12 | S 7 6
W S 13 | S 18 W
1967

from which the remaining Lake and Hyde bearing trees:

- A fir, 40 ins. diam., bears S. 22° E., 12 lks. dist., with scribe marks BT visible on partially opened blaze.
- A cedar, 27 ins. diam., bears N. 27° W., 28 lks. dist., with partial scribe marks visible on partially open blaze.

and bearing trees mkd. by the County Surveyor