

14498 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 31 S., R. 7 W.

CHAINS

A fir, 22 ins. diam., bears N. $40\frac{1}{2}^\circ$ E., $35\frac{1}{2}$ lks. dist., with scribe marks T31S R6W S7 CS BT visible on open blaze.

A cedar, 15 ins. diam., bears S. 22° W., 45 lks. dist., with scribe marks T31S R7W S13 CS BT visible on open blaze.

A cedar, 13 ins. diam., bears N. 65° W., 24 lks. dist., with scribe marks T31S R7W S12 CS BT visible on open blaze.

N. $0^\circ 44'$ E., beginning new measurement.

Descend 355 ft. over NW. slope.

8.90 Island Creek, 4 lks. wide, course N. 70° W.; asc. 130 ft. over SW. slope.

14.50 Top of ascent, slopes W.; desc. 85 ft. over NW. slope.

17.60 Creek, 2 lks. wide, course W; asc. 285 ft. over SW. slope.

33.85 Spur, slopes W.; desc. 95 ft. over NW. slope.

37.35 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 12 | S 7
 R 7 W | R 6 W
 T 31 S
 1969

from which

A fir, 9 ins. diam., bears N. 49° E., 49 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

A fir, 8 ins. diam., bears S. 11° W., $56\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S12 BT.

Descend 300 ft. over NW. slope.

46.05 Creek, 2 lks. wide, course W.; asc. 185 ft. over SW. slope.

53.60 Ravine, drains S. 15° W.; asc. 535 ft. over SW. slope.

75.30 Ridge, bears N. 60° W. and S. 60° E.; desc. 40 ft. over NE. slope.

77.31 Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S
 R 7 W | R 6 W
S 1 | S 6
 S 12 | S 7
 1969

from which