

County Surveyor's Record, Douglas County, Oregon

14497

Dependent Resurvey, Portion of E. Bdy., T. 31 S., R. 7 W.

CHAINS

- A fir, 5 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ E., 61 lks. dist., mkd. T31S R6W S6 BT.
- A fir, 14 ins. diam., bears S. $83\frac{1}{2}^{\circ}$ E., $55\frac{1}{2}$ lks. dist., mkd. T31S R6W S7 BT.
- A fir, 25 ins. diam., bears S. 24° W., 98 lks. dist., mkd. T31S R7W S12 BT.
- A madrone, 8 ins. diam., bears N. 49° W., 106 lks. dist., mkd. T31S R7W S1 BT.

Land, mountainous.
 Soil, rocky clay loam.
 Timber, fir, cedar, hemlock, madrone, alder, and oak; undergrowth, poison oak, salal, hazel, fern, and vine maple.

N. 0° 44' E., bet. secs. 1 and 6.

Descend 445 ft. over NE. slope, through moderate timber and undergrowth.

- 14.45 Ravine, drains E.; asc. 130 ft. over SE. slope.
- 22.55 Spur, slopes E; desc. 305 ft. over NE. slope.
- 33.30 Draw, drains N. 45° E.; asc. 35 ft. over SE. slope.
- 36.20 Spur, slopes E.; desc. 160 ft. over NE. slope.
- 39.96 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mdk.

$\frac{1}{4}$
 S 1 | S 6
 R 7 W R 6 W
 T 31 S
 1969

*FD. OK 6/88
 H. JOHNSTONE
 M106-52*

from which

- A fir, 32 ins. diam., bears S. 88° E., $75\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S6 BT.
- A madrone, 8 ins. diam., bears N. $55\frac{3}{4}^{\circ}$ W., 86 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Descend 85 ft. over NE. slope.

- 43.15 Ravine, drains N. 60° E.; asc. 110 ft. over SE. slope.
- 47.60 Spur, slopes E.; desc. 320 ft. over NE. slope.
- 56.35 Ravine, drains N. 70° E.; asc. 65 ft. over SE. slope.
- 59.94 Point for the N 1/16 sec. cor. of secs. 1 and 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
 S 1 | S 6
 1969

from which