

# 14498 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 31 S., R. 7 W.

CHAINS

A fir, 20 ins. diam., bears N. 84° E., 29 lks. dist.,  
mkd. N 1/16 S6 BT.

A fir, 8 ins. diam., bears N. 74½° W., 49 lks. dist.,  
mkd. N 1/16 S1 BT.

Ascend 5 ft. over SE. slope.

61.60 Spur, slopes E.; desc. 60 ft. over NE. slope.

63.60 Ravine, drains E.; asc. 30 ft. over SE. slope.

65.60 Spur, slopes E.; desc. 150 ft. over NE. slope.

73.30 Ravine, drains E.; asc. 35 ft. over SE. slope.

74.85 Spur, slopes E.; desc. 165 ft. over NE. slope.

81.81 The cor. of Tps. 30 and 31 S., Rs. 6 and 7 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap, mkd. and witnessed as described in the official record of a 1965 dependent resurvey.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, alder, maple, pine, and madrone;  
undergrowth, salal, hazel, poison oak, Oregon grape and fern.

Dependent Resurvey of a Portion of the N. Bdy.  
T. 31 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1872 survey by William H. Byars)

N. 89° 58' W., bet. secs. 1 and 36, marking and blazing the true line.

Ascend 545 ft. over NE. slope, through moderate timber and undergrowth.

18.40 Top of ascent, slopes N.; desc. 95 ft. over NW. slope.

24.25 Ravine, drains N. 20° W.; asc. 35 ft. over NE. slope.

30.00 Spur, slopes N. 60° W.; desc. 320 ft. over NW. slope.

38.20 Ravine, drains N. 30° W.; asc. 35 ft. over N. slope.

40.74 Point for the ¼ sec. cor. of secs. 1 and 36; at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with a brass cap mkd.

T 30 S  
¼ S 36  
¼ S 1  
T 31 S R 7 W  
1969

from which