

14500 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 7 W.

CHAINS

81.48

Point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 7 W
 $\frac{S 35}{S 2} | \frac{S 36}{S 1}$
 T 31 S
 1969

from which

A fir, 30 ins. diam., bears N. 14° E., 120 lks. dist., mkd. T30S R7W S36 BT.

A cedar, 12 ins. diam., bears S. 12° E., $32\frac{1}{2}$ lks. dist., mkd. T31S R7W S1 BT.

A fir, 17 ins. diam., bears S. $76\frac{1}{2}^\circ$ W., $52\frac{1}{2}$ lks. dist., mkd. T31S R7W S2 BT.

A fir, 20 ins. diam., bears N. $13\frac{3}{4}^\circ$ W., 82 lks. dist., mkd. T30S R7W S35 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, alder, and oak; undergrowth, salal, fern, poison oak, hazel, and Oregon grape.

N. $89^\circ 58'$ W., bet. secs. 2 and 35.

Descend 1 ft. over N. slope, through moderate timber and moderate undergrowth.

1.00

Creek, 3 lks. wide, course N. 30° E.; asc. 325 ft. over broken E. slope.

20.37

Point for the E $\frac{1}{16}$ sec. cor. of secs. 2 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

E $\frac{1}{16}$ $\frac{S 35}{S 2}$
 1969

from which

A fir, 25 ins. diam., bears N. $60\frac{3}{4}^\circ$ W., 50 lks. dist., mkd. E $\frac{1}{16}$ S35 BT.

A fir, 15 ins. diam., bears S. $32\frac{1}{2}^\circ$ W., 13 lks. dist., mkd. E $\frac{1}{16}$ S2 BT.

Ascend 440 ft. over broken E. slope.

40.74

Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S
 $\frac{1}{4} \frac{S 35}{S 2}$
 T 31 S R 7 W
 1969