

County Surveyor's Record, Douglas County, Oregon

14502

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 7 W.

CHAINS

by the Douglas County Surveyor in 1966, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R T 31 S
7 S 14 | S 13
W |
¼ 1966

from which the original bearing trees

A fir snag, 50 ins. diam., bears N. 50° E., 19 lks. dist., with scribe marks ¼ S BT visible on bark blaze. (Record, 16 lks.)

A fir snag, 45 ins. diam., bears S. 45° W., 52 lks. dist., with no marks remaining on burned bark blaze. (Record, 50 lks.)

and bearing trees mkd. by the County Surveyor

A cedar, 10 ins. diam., bears S. 52½° E., 18 lks. dist., with scribe marks ¼ S13 CS BT visible on open blaze.

A root hole, bears N. 61½° W., 52 lks. dist., with a down fir, 8 ins. diam., alongside, with scribe marks ¼ S14 CS BT visible on open blaze.

and new bearing trees

A fir, 9 ins. diam., bears S. 15½° E., 33½ lks. dist., mkd. ¼ S13 BT.

A fir, 25 ins. diam., bears N. 8¼° W., 53 lks. dist., mkd. ¼ S14 BT.

N. 0° 45' E., bet. secs. 13 and 14, marking and blazing the true line.

Descend 185 ft. over NW. slope, through moderate timber and dense undergrowth.

10.70 Ravine, drains N. 70° W.; asc. 35 ft. over SW. slope.

13.20 Spur, slopes W.; desc. 50 ft. over NW. slope.

14.25 Ravine, drains N. 70° W.; asc. 45 ft. over SW. slope.

19.75 Top of ascent, slopes W.; desc. 260 ft. over N. slope.

27.35 Iron Mountain Creek, 3 lks. wide, course N. 60° W.; asc. 190 ft. over SW. slope.

41.89 The cor. of secs. 11, 12, 13, and 14, determined at record distance from the remaining original bearing trees:

A root hole, bears S. 7° E., 29 lks. dist., with a down fir, 15 ins. diam., alongside, with scribe marks T31S R7W S13 BT visible on bark blaze.

A fir, 35 ins. diam., bears N. 51½° W., 54 lks. dist., with no marks remaining on opened blaze. (Record, N. 48°W.)

At the corner point