

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 7 W  
 S 11 | S 12  
 S 14 | S 13  
 1969

from which new bearing trees

A fir, 5 ins. diam., bears N. 70½° E., 35½ lks. dist., mkd. T31S R7W S12 BT.

A fir, 8 ins. diam., bears S. 61½° E., 52 lks. dist., mkd. T31S R7W S13 BT.

A fir, 9 ins. diam., bears S. 56½° W., 35 lks. dist., mkd. T31S R7W S14 BT.

A fir, 4 ins. diam., bears N. 42 3/4° W., 78 lks. dist., mkd. T31S R7W S11 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, pine, alder, and oak; undergrowth, salal, hazel, fern, poison oak, and Oregon grape.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.

N. 89° 27' W., bet. secs. 12 and 13.

Descend 385 ft. over SW. slope, through moderate timber and dense undergrowth.

9.35 Creek, 4 lks. wide, course N. 30° E.; asc. 490 ft. over E. slope.

27.00 Ravine, drains N. 60° E.; asc. 300 ft. over SE. slope.

40.18 The ¼ sec. cor. of secs. 12 and 13, perpetuated and recorded by the Douglas County Surveyor in 1962, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 31 S R  
 S 12 7  
 S 13 W  
 ¼ 1962

from which the original bearing trees:

A fir stump, 20 ins. diam., bears N. 26° E., 23 lks. dist., with fragmentary scribe marks visible on open blaze, remarked by the County Surveyor, ¼ S12 CS BT alongside the original blaze.

A fir, 20 ins. diam., bears S. 12° W., 39 lks. dist., with no marks visible on open blaze.

and a bearing tree mkd. by the County Surveyor

A cedar, 23 ins. diam., bears S. 59° E., 61½ lks. dist., with scribe marks ¼ S13 CS BT visible on open blaze.