

# County Surveyor's Record, Douglas County, Oregon

14508

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 7 W.

CHAINS

A root hole, bears N. 23° E., 40 lks. dist., with a down madrone, 13 ins. diam., alongside with fragmentary scribe marks visible in negative on overgrowth. (Record, N. 30° E.)

A fir, 27 ins. diam., bears S. 27° W., 14 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on bark blaze. (Record, S. 21° W.)

At the corner point

Set an iron post, 28 ins. long  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 11}{S\ 14}$   
 T 31 S R 7 W  
 1969

from which new bearing trees

A fir, 8 ins. diam., bears N. 18° E., 85 lks. dist., mkd.  $\frac{1}{4}$  S11 BT.

A fir, 17 ins. diam., bears S. 59° E.,  $29\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S14 BT.

Land, mountainous.

oil, rocky clay loam.

Timber, fir, hemlock, pine, cedar, alder, and oak; undergrowth, salal, fern, poison oak, hazel, and Oregon grape.

From the cor. of secs. 1, 2, 11, and 12.

S. 89° 23' W., bet. secs. 2 and 11.

Ascend 35 ft. over NE. slope, through moderate timber and dense undergrowth.

- 1.05 Spur, slopes N.; desc. 20 ft. over NW. slope.
- 1.75 Creek, 2 lks. wide, course N. 50° E.; asc. 350 ft. over SE. slope.
- 13.55 Ravine, drains S. 45° E.; asc. 370 ft. over E. slope.
- 26.35 Ridge, bears N. 20° W. and S. 20° E.; desc. 255 ft. over W. slope.
- 27.75 Jeep road, 10 lks. wide, bears N. 10° W., in curve to W., and S. 10° E., in curve to E.
- 39.90 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, perpetuated and recorded by the Douglas County Surveyor in 1962, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R  
 S 2 7  
 $\frac{1}{4}$   $\frac{S\ 11}{S\ 11}$  W  
 1962

from which the original bearing trees: