

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 7 W.

CHAINS

A burned fir snag, size indeterminate, bears N. 38° W., 52 lks. dist., with no marks remaining. (Record, 60 lks.; 60 lks. on the slope)

A pine, 40 ins. diam., bears S. 55° W., 46 lks. dist., with no scribe marks visible on burned blaze. Remarkd $\frac{1}{4}$ S11 CS BT alongside the original blaze by the County Surveyor.

and a bearing tree mkd. by the County Surveyor

A madrone, 10 ins. diam., bears N. 27° E., 24 lks. dist., with scribe marks $\frac{1}{4}$ S2 CS BT visible on open blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, madrone, pine, alder, and oak; undergrowth, salal, hazel, fern, poison oak, and Oregon grape.

The following field notes describe the remonumentation of a certain original corner point, T. 31 S., R. 7 W., as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

(Remonumenting a corner established by William H. Byars in 1882)

The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by the County Surveyor in 1962, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, from which the remaining original bearing trees:

A root hole, bears N. 30° E., 39 lks. dist., with a down fir, 14 ins. diam., alongside, with fragmentary scribe marks visible on decayed blaze.

A fir, 42 ins. diam., bears N. 20° W., 40 lks. dist., with fragmentary scribe marks visible on bark blaze. Remarkd T31S R7W S14 on bark alongside the original blaze by the County Surveyor.

And bearing trees mkd. by the County Surveyor

A fir, 31 ins. diam., bears S. 80° E., 25 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 17 ins. diam., bears S. 27° W., 103 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
 S 14 | S 13
 S 23 | S 24
 1969

from which new bearing trees