

T. 30 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of that portion of township 30 south, range 2 west, Willamette Meridian, Oregon, included in the following resurvey, is as follows:

A portion of the west boundary was surveyed by William M. Bushey in 1893-94, as shown on the official plat of survey approved June 29, 1895. A portion of the west boundary was resurveyed by Fred Mensch in 1909, as shown on the official plat of survey approved October 14, 1910. The subdivisional lines were surveyed by Fred Mensch, in 1909, as shown on the official plat of survey approved October 14, 1910.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding, or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated August 24, 1970, under Group 705, Oregon.

The directions of the lines were determined by the solar transit method and by direct solar observations.

The geographic position of the southeast corner of section 7, as scaled from the Tiller, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1944, is as follows:

Latitude 42° 58.6' N.                      Longitude 122° 58.9' W.

The mean magnetic declination is 20° E.

Dependent Resurvey of a Portion of the W. Bdy., T. 30 S.,  
R. 2 W., Willamette Meridian, Oregon

(Restoring the 1893 Survey of W. A. Bushey and the 1909 Resurvey  
by Fred Mensch)

From the cor. of secs. 12 and 13 only, on the E. bdy. of T. 30 S., R. 3 W., perpetuated and recorded by the Douglas County Surveyor, in 1965, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground, from which the original bearing trees:

A cedar, 21 ins. diam., bears S. 41° W., 16 lks. dist.,  
with healed blaze. (Record, S. 33° W.)

A cedar, 33 ins. diam., bears N. 48° W., 48 lks. dist.,  
with healed blaze. (Record, N. 46 3/4° W.)

and trees by the County Surveyor

A cedar, 21 ins. diam., bears S. 45° W., 27 lks. dist.,  
with scribe marks T30S R3W S13 CS BT visible on open  
double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground, with brass cap mkd.