

# County Surveyor's Record, Douglas County, Oregon

14512

Dependent Resurvey, Portion of the W. Bdy., T. 30 S., R. 2 W.

CHAINS

T 30 S  
R 3 W | R 2 W  
S 12 | S 18  
S 13 |  
1970

Reset iron pipe alongside iron post.

N. 0° 22' W., along the E. bdy. of sec. 12, marking and blazing true line.

Ascend 20 ft. over S. slope, through moderate timber and dense undergrowth, along E. edge of logged area.

0.71 True point for the closing cor. of secs. 7 and 18, T. 30 S., R. 2 W., hereinafter described.

Ascend 55 ft. over S. slope.

4.95 Spur, slopes W.; desc. 50 ft. over N. slope.

8.05 Creek, 1 lk. wide, course NE.; asc. 75 ft. over SE. slope.

15.70 Spur, slopes SE.; desc. 10 ft. over NE. slope.

17.40 Creek, 2 lks. wide, course SE.; asc. 90 ft. over SE. slope.

20.605 Point for the S 1/16 sec. cor. of sec. 7 only, on the E. bdy. of T. 30 S., R. 3 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16  
S 7  
1970

from which

A fir, 16 ins. diam., bears N. 46 ¾° E., 66 lks. dist.,  
mkd. S 1/16 S7 BT.

A pine, 17 ins. diam., bears S. 62½° E., 103 lks. dist.,  
mkd. S 1/16 S7 BT.

Ascend 140 ft. over SE. slope.

32.85 Spur, slopes E.; desc. 20 ft. over NE. slope.

35.30 Head of ravine, drains E.; asc. 40 ft. over SE. slope.

39.30 Spur, slopes E.; desc. 30 ft. over NE. slope.

40.50 The ¼ sec. cor. of secs. 7 and 12, perpetuated and recorded by the Douglas County surveyor, in 1963, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S  
S 12 | S 7  
¼ R | R  
3 | 2  
W | W  
1963