

14515 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 30 S R 2 W
S 7

S 18 | S 17
1963

from which the original bearing trees

A fir, 20 ins. diam., bears S. 38° E., 34 lks. dist., with healed blaze.

A hemlock snag, 24 ins. diam., bears S. 11½° W., 51 lks. dist., with scribe marks S18 visible on partially healed blaze. (Record, S. 18° W.)

and trees by the County Surveyor

A cedar, 12 ins. diam., bears N. 21 3/4° E., 38 lks. dist, with scribe marks T30S R2W S7 CS BT visible on open double blaze.

A hemlock, 12 ins. diam., bears S. 53° W., 19 lks. dist., with scribe marks T30S R2W S18 CS BT visible on open double blaze.

N. 89° 51' W., beginning new measurement.

Descend 25 ft. over SW. slope.

- 0.70 Creek, 2 lks. wide, course NW.; asc. 10 ft. over NW. slope.
- 1.38 Spur, slopes NW.; desc. 115 ft. over NW. slope.
- 8.80 Ruby Creek, 2 lks. wide, course S. 50° W.; asc. 20 ft. over SE. slope.
- 12.35 Spur, slopes S.; desc. 20 ft. over SW. slope.
- 14.85 Ravine, drains S.; asc. 30 ft. along SE. slope.
- 19.20 Spur, slopes S.; desc. 55 ft. over SW. slope
- 23.80 Ravine, drains S.; asc. 50 ft. over SE. slope.
- 27.80 Spur, slopes S.; desc. 35 ft. over SW. slope.
- 30.15 Ravine, drains S.; asc. 60 ft. over SE. slope.
- 36.05 Spur, slopes NE.; desc. 75 ft. over NW. slope.
- 38.25 The ¼ sec. cor. of sec. 7 only, monumented by the original cor. tree, a fir, 40 ins. diam., with scribe marks ¼ S7 visible on open blaze on N., and healed blaze on S. face, from which the original bearing trees:
 - A fir stump, 38 ins. diam., bears N. 43° E., 91 lks. dist., with scribe marks ¼ S7 BT visible on opened blaze.
 - A fir stump, 37 ins. diam., bears N. 68° W., 28 lks. dist., with scribe marks ¼ S7 BT visible on opened blaze.

From this point, reference monument, established by the Douglas