

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

County Surveyor, in 1959, bears East, 8 lks. dist., monumented with an iron post,  $1\frac{1}{2}$  ins. diam., firmly set, projecting  $1\frac{1}{4}$  ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

Wit Cor  
5 ft W To  
 $\frac{1}{4}$  S 7

T 30 S R 2 W  
1959

from which

A fir, 9 ins. diam., bears N.  $46^\circ$  E., 43 lks. dist., with healed double blaze.

A fir, 10 ins. diam., bears N.  $3^\circ$  W., 36 lks. dist., with healed double blaze.

---

S.  $87^\circ 16'$  W., beginning new measurement.

Descend 60 ft. over NW. slope.

1.72 The  $\frac{1}{4}$  sec. cor. of sec. 18 only, monumented with an iron pin  $\frac{3}{4}$  in. diam., firmly set, projecting 12 ins. above ground, from which the original bearing tree:

A fir stump. 34 ins. diam., bears S.  $21^\circ$  W., 39 lks. dist., with fragmentary scribe marks visible on open blaze.

and a tree of which I have no record

A pine, 32 ins. diam., bears N.  $50^\circ$  W., 5 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T 30 S R 2 W

$\frac{1}{4}$  S 18  
1970

from which a new bearing tree

A fir, 8 ins. diam., bears S.  $75^\circ$  W., 36 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

Reset the iron pin alongside the iron post.

---

N.  $89^\circ 42'$  W., beginning new measurement.

Descend 140 ft. over NW. slope.

5.80 Granite Creek, 5 lks. wide, course SW.; asc. 15 ft. over SE. slope.

8.10 Spur, slopes SW.; desc. 25 ft. over W. slope.

8.70 Barbed wire fence, bears NE. and SW.