

County Surveyor's Record, Douglas County, Oregon

14517

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

- 10.60 Woven wire fence, bears N. and S.
- 11.10 Gravelled road, 10 lks. wide, bears NE. and S.
- 12.70 Coffee Creek, 10 lks. wide, course S.; asc. 75 ft. over SE. slope.
- 17.70 Gravelled road, 15 lks. wide, bears NE. and SW.
- 18.21 Point for the W 1/16 sec. cor. of sec. 7 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 7
1970

from which

A fir, 12 ins. diam., bears N. 25° E., 84 lks. dist.,
mkd. W 1/16 S7 B¹.

A fir, 8 ins. diam., bears North, 2½ lks. dist., mkd.
W 1/16 S7 BT.

Ascend 15 ft. over SE. slope.

- 21.07 From this point, an iron bolt, 1 in. diam., bears North, 62 lks. dist., firmly set, projecting 6 ins. above the ground.
- 21.70 Creek, 2 lks. wide, course SE.; asc. 215 ft. over SE. slope.
- 33.60 Spur, slopes S.; desc. 20 ft. over W. slope.
- 35.80 Ravine, drains S.; asc. 20 ft. over SE. slope.
- 37.20 Spur, slopes S.; desc. 20 ft. over SW. slope.
- 39.78 Ravine, drains SE.; asc. 5 ft. along S. slope.
- 40.98 Intersect the E. bdy. of T. 30 S., R. 3 W.

The true point for closing cor. of secs. 7 and 18, established by the Douglas County Surveyor in 1963, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
R | R
3 CC | S 7 2
W | S 18 W
 1963

from which a tree by the County Surveyor

A fir, 8 ins. diam., bears S. 60¼° E., 69 lks. dist.,
with healed blaze.

and a new bearing tree

A fir, 5 ins. diam., bears N. 56½° E., 89 lks. dist.,
mkd. T30S R2W S7 CC BT.

From this point, the original closing cor. of secs. 7 and 18, bears N. 89° 42' W., 4 lks. dist., monumented with an iron rod,