

# County Surveyor's Record, Douglas County, Oregon 14518

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 2 W.

**CHAINS**

$\frac{1}{2}$  in. diam., firmly set, projecting 6 ins. above the ground, from which the remaining original bearing tree:

A root hole, bears S. 52° E., 14 lks. dist., with a down fir alongside, 16 ins. diam., with fragmentary scribe marks visible on open blaze.

From this same point, the cor. of secs. 12 and 13 only, T. 30 S., R. 3 W., bears S. 0° 22' E., 71 lks. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, pine, maple, oak, chinquapin, dogwood, cascara, madrone and yew; undergrowth, poison oak, manzanita, fern, blackberry, vine maple, hazel, willow, Oregon grape, salal, huckleberry, arrowwood and wild rose.

From the cor. of secs. 7 and 8 only.

N. 0° 04' W., bet. secs. 7 and 8.

Descend 85 ft. over NW. slope, through light timber and dense undergrowth.

- 5.30 Ruby Creek, 3 lks. wide, course SW.; asc. 90 ft. over SE. slope.
- 8.70 Spur, slopes SW.; asc. 10 ft. over SE. slope.
- 11.10 Ravine, drains SW.; asc. 105 ft. over SE. slope.
- 16.35 Dirt road, 10 lks. wide, bears NE. and SW.
- 17.15 Spur, slopes SW.; desc. 300 ft. over NW. slope.
- 37.20 Creek, 1 lk. wide, course W.; desc. 30 ft. over NW. slope.
- 37.40 Dirt road, 20 lks. wide, bears E. and W.
- 38.30 Mining ditch, 3 lks. wide, bears E. and W.
- 38.55 Creek, 3 lks. wide, course W.; asc. 40 ft. over SW. slope.
- 40.20 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 2 W  
 $\frac{1}{4}$   
 S 7 | S 8  
 1970

from which

A pine, 13 ins. diam., bears N. 57° E., 28 lks. dist., mkd.  $\frac{1}{4}$  S8 BT.

A white fir, 9 ins. diam., bears N. 60 $\frac{1}{2}$ ° W., 34 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.