

# County Surveyor's Record, Douglas County, Oregon

14519

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

From this point, an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, bears S. 0° 06' E., 27 lks. dist.

Ascend 160 ft. over SW. slope.

44.80 Spur, slopes SW.; desc. 130 ft. over broken NW. slope.

60.30 Point for the N 1/16 sec. cor. of secs. 7 and 8.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16  
S 7 | S 8  
1970

from which

A fir, 8 ins. diam., bears S. 28° E., 81 lks. dist.,  
mkd. N 1/16 S8 BT.

A fir, 12 ins. diam., bears N. 83° W., 62 lks. dist.,  
mkd. N 1/16 S7 BT.

Descend 40 ft. over broken NW. slope.

65.50 Dirt road, 15 lks. wide, bears NE. and SW.

69.90 Granite Creek, 4 lks. wide, course SW.; asc. 225 ft. over SE. slope.

75.55 Mining ditch, 1 lk. wide, bears NE. and SW.

80.40 The cor. of secs. 5, 6, 7 and 8, perpetuated and recorded by the Douglas County Surveyor, in 1963, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 14 ins. above the ground, from which the original bearing trees:

A madrone, 21 ins. diam., bears N. 75½° E., 24 lks. dist., with scribe marks T30S R2W S5 visible on open blaze. (Record, N. 86° E., 30 lks.)

A fir, 33 ins. diam., bears S. 43½° E., 42 lks. dist., with scribe marks S8 BT visible on bark. (Record, S. 40½° E., 40 lks.)

A madrone, 12 ins. diam., bears S. 23½° W., 37 lks. dist., no marks remaining on rotted blaze.

A madrone, 20 ins. diam., bears N. 70° W., 28 lks. dist., with scribe marks S6 BT visible on bark. (Record, N. 66° W.)

and trees by the County Surveyor

A fir, 6 ins. diam., bears S. 15° W., 11 lks. dist., with scribe marks C S S7 BT visible on partially healed double blaze.

A madrone, 12 ins. diam., bears N. 1° W., 28 lks. dist., with scribe marks T30S R2W S5 C S BT visible on open blaze.

at the corner point