

County Surveyor's Record, Douglas County, Oregon

14521

Dependent Resurvey, Portion of Subdivisional Lines, T. 30 S., R. 2 W.

CHAINS

diam., firmly set, projecting 8 ins. above the ground, perpetuated and recorded by the Douglas County Surveyor, in 1967, from which the remaining original bearing tree:

A pine, 37 ins. diam., bears N. $80\frac{1}{2}^\circ$ E., 65 lks. dist., with healed blaze.

and trees by the County Surveyor

A fir, 25 ins. diam., bears S. $89\frac{1}{2}^\circ$ W., 136 lks. dist., with scribe marks $\frac{1}{4}$ S7 C S BT visible on open blaze.

A twin madrone, 19 ins. diam., bears N. 1° W., 48 lks. dist., with scribe marks $\frac{1}{4}$ S6 C S BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 2 W
 $\frac{1}{4}$ $\frac{S 6}{S 7}$
1970

Deposit the original stone and reset the iron pipe alongside the iron post.

S. $89^\circ 57'$ W., beginning new measurement.

Descend 5 ft. along S. slope, through open field.

2.50 Bottom of desc., slopes SE.; asc. 5 ft. over SE. slope.

5.00 Spur, slopes S.; desc. 545 ft. over W. slope; leave open field, edges bear N. and S.

20.19 Point for the W $\frac{1}{16}$ sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W $\frac{1}{16}$ $\frac{S 6}{S 7}$
1970

from which

A hemlock, 15 ins. diam., bears N. $22\frac{1}{4}^\circ$ E., 75 lks. dist., mkd. W $\frac{1}{16}$ S6 BT.

A fir, 6 ins. diam., bears S. $0^\circ 3/4'$ W., 72 lks. dist., mkd. W $\frac{1}{16}$ S7 BT.

Descend 190 ft. over W. slope.

22.50 Gravelled road, 10 lks. wide, bears N. and S.

23.10 Coffee Creek, 15 lks. wide, course S.; asc. 15 ft. over E. slope.

25.00 Prospecting hole, 6 ft. diam., 5 ft. deep, on line.

25.60 Top of ascent, bears N. and S.; desc. 5 ft. over SW. slope.