

County Surveyor's Record, Douglas County, Oregon

14523

Subdivision of Section 7, T. 30 S., R. 2 W.

CHAINS

with the E. and W. center line of sec. 7.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{1}{4}$ S 7
1970

from which

A fir, 10 ins. diam., bears N. 52° E., 75 lks. dist.,
mkd. C $\frac{1}{4}$ S7 BT.

A fir, 48 ins. diam., bears S. $38\frac{3}{4}^\circ$ W., 109 lks.
dist., mkd. C $\frac{1}{4}$ S7 BT.

Ascend 200 ft. over SW. slope.

44.65 Barbed wire fence, bears NE. and SW.

54.20 Corner of fences, extends N. and E.

55.50 Corner of fences, extends S. and E.; enter open field,
edges bear E. and W.

59.96 Point for the center N $1/16$ sec. cor. of sec. 7.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N $1/16$ | S 7
C
1970

from which

A pine, 30 ins. diam., bears S. $18\frac{1}{4}^\circ$ E., 474 lks.
dist., mkd. CN $1/16$ S7 BT.

A fir, 17 ins. diam., bears S. 32° W., 357 lks. dist.,
mkd. CN $1/16$ S7 BT.

Ascend 265 ft. over SW. slope.

67.70 Old fence line, bears S. 10° E. and N. 10° W.; enter
moderate timber and undergrowth.

73.40 East edge of pond, 170 lks. wide, edges bear N. 70° E.; and S.
 70° W.

75.80 Corner of fences extends E. and SW.; enter open field, edges
bear E. and W.

79.90 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

S. $89^\circ 55'$ W., on the E. and W. center line of sec. 7.

Descend 10 ft. over SW. slope, through light timber and moderate
undergrowth.

0.95 Ravine, drains S.; asc. 35 ft. over SE. slope.

2.55 Spur, slopes S.; desc. 160 ft. over SW. slope.

10.15 Dirt road, 10 lks. wide, bears N. 70° E. and SW.