


Subdivision of Section 7, T. 30 S., R. 2 W.

CHAINS

- 12.60 Slope changes to NW.; continue descent.
- 15.25 Granite Creek, 3 lks. wide, course SW.; asc. 165 ft. over SE. slope.
- 18.70 Enter heavy timber and moderate undergrowth, edges bear NE. and SW.
- 19.97 Point for the center E 1/16 sec. cor. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




from which

A fir, 15 ins. diam., bears N. 52 3/4° E., 26 lks. dist., mkd. CE 1/16 S7 BT.

A fir, 16 ins. diam., bears S. 37¼° W., 54 lks. dist., mkd. CE 1/16 S7 BT.

Ascend 135 ft. over SE. slope.

- 25.50 Spur, slopes S. 20° W.; desc. 130 ft. over SW. slope.
- 33.00 Creek, 1 lk. wide, course S.; asc. 110 ft. over SE. slope.
- 36.30 Dirt road, 20 lks. wide, bears N. and S., curving W.
- 36.80 Spur, slopes S.; desc. 35 ft. over SW. slope.
- 39.94 The center ¼ sec. cor. of sec. 7.
- Descend 70 ft. over SW. slope.
- 42.20 Creek, 1 lk. wide, course S.; asc. 110 ft. over SE. slope.
- 48.30 Spur, slopes SW.; desc. 70 ft. over SW. slope.
- 51.15 Head of ravine, drains SW.; desc. 220 ft. over SW. slope.
- 60.01 Point for the center W 1/16 sec. cor. of sec. 7,
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 25 ins. diam., bears N. 68° E., 10 lks. dist., mkd. CW 1/16 S7 BT.

A fir, 27 ins. diam., bears S. 30¼° W., 20 lks. dist., mkd. CW 1/16 S7 BT.

Descend 55 ft. over SW. slope.

- 62.20 Gravelled road, 15 lks. wide, bears N. and S.