

County Surveyor's Record, Douglas County, Oregon

14525

Subdivision of Section 7, T. 30 S., R. 2 W.

CHAINS

- 64.60 Coffee Creek, 25 lks. wide, course S; asc. 20 ft. over NE. slope.
- 65.65 Creek, 1 lk. wide, course SE.; asc. 120 ft. over NE. slope.
- 67.70 Mining ditch, 1 lk. wide, bears N. and S.
- 70.70 Creek, 1 lk. wide, course N. 70° E.; asc. 35 ft. over NE. slope.
- 71.40 Creek, 1 lk. wide, course S. 80° E.; asc. 365 ft. over NE. slope.
- 82.91 The $\frac{1}{4}$ sec.cor. of secs. 7 and 12.

From the center E $\frac{1}{16}$ sec. cor. of sec. 7.

N. 0° 03' W., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 7.

Ascend 180 ft. over S. slope, through moderate timber and undergrowth.

- 7.60 Top of ascent, bears N. and S.; desc. 5 ft. over NE. slope.
- 8.70 Bottom of descent, drains SE.; asc. 40 ft. over S. slope.
- 11.75 Spur, slopes S.; desc. 5 ft. over NE. slope.
- 12.95 Ravine, drains SE.; asc. 15 ft. over S. slope.
- 20.00 Point for the NE $\frac{1}{16}$ sec. cor. of sec. 7, at intersection with the E. and W. center line of the NE $\frac{1}{4}$ of sec. 7.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

NE $\frac{1}{16}$ S7
1970

from which

A fir, 12 ins. diam., bears N. 25° E., 15 lks. dist.,
mkd. NE $\frac{1}{16}$ S7 BT.

A fir, 13 ins. diam., bears S. 7° E., 66 lks. dist.,
mkd. NE $\frac{1}{16}$ S7 BT.

Ascend 85 ft. over S. slope.

- 29.10 Spur, slopes E.; desc. 85 ft. over NW. slope.
- 32.15 Ravine, drains N. 60° E.; asc. 30 ft. over SE. slope.
- 35.10 Spur, slopes N. 60° E.; desc. 15 ft. over NE. slope.
- 38.10 Bottom of descent, drains SE.; asc. 40 ft. over S. slope.
- 40.02 The E $\frac{1}{16}$ sec. cor. of secs. 6 and 7.

From the N $\frac{1}{16}$ sec. cor. of secs. 7 and 8.

S 89° 42' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 7.