

Subdivision of Section 7, T. 30 S., R. 2 W.

CHAINS

- Descend 80 ft. over SW. slope, through moderate timber and undergrowth.
- 2.45 Dirt road, 20 lks. wide, bears N. 10° E. and S. 10° W.
- 5.10 Granite Creek, 6 lks. wide, course SE., curving SW.; asc. 235 ft. over SE. slope.
- 13.95 Spur, slopes S. 40° E.; desc. 30 ft. over SW. slope.
- 16.20 Creek, 1 lk. wide, course S. 20° E.; asc. 100 ft. over SE. slope.
- 19.97 The NE 1/16 sec. cor. of sec. 7.
Ascend 42 ft. over SE. slope.
- 23.90 Old logging road, 15 lks. wide, bears N. and S.
- 25.45 Spur, slopes S.; desc. 105 ft. over SW. slope.
- 31.15 Creek, 1 lk. wide, course S.; asc. 115 ft. over E. slope.
- 35.40 Dirt road, 15 lks. wide, bears N. and S.; enter open field, edges bear same as road.
- 35.65 Barbed wire fence, bears N. and S.
- 36.45 Top of ascent, slopes S.; desc. a slight SW. slope.
- 37.35 Woven wire fence, bears N. and S.
- 39.95 The center N 1/16 sec. cor. of sec. 7.
-
- From the W 1/16 sec. cor. of sec. 7 only.
- N. 0° 12' W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 7.
- Ascend 5 ft. over S. slope.
- 1.30 Spur, slopes E.; desc. 35 ft. over N. slope.
- 3.25 Gravelled road, 20 lks. wide, bears S. 25° E. and N. 25° W.
- 6.75 Bottom of descent, drains E.; asc. 15 ft. over S. slope.
- 7.25 Gravelled road, 20 lks. wide, bears NE. and SW.
- 9.85 Spur, slopes E.; desc. 40 ft. over S. slope.
- 12.30 Gravelled road, 15 lks. wide, bears SE. and N^W.
- 14.90 Coffee Creek, 12 lks. wide, course SE.; asc. 10 ft. over S. slope.
- 16.35 Same Creek, 12 lks. wide, course W.; continue ascent.
- 19.97 Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ of sec. 7. This point falls in the center of Coffee Creek, 12 lks. wide, course S. 25° E., where it is impractical to establish a permanent monument.
Ascend 5 ft. over SW. slope.
- 20.34 Point selected for the witness SW 1/16 sec. cor. of sec. 7.