

Subdivision of Section 7, T. 30 [~], R. 2 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to otop, with brass cap mkd.

W C
SW $\frac{1}{16}$ S 7
↓
1970

from which

A fir, 19 ins. diam., bears N. $3\frac{1}{4}^{\circ}$ E., 119 lks. dist., mkd. X BT on double blaze.

A fir, 22 ins. diam., bears S. $38\frac{1}{2}^{\circ}$ E., 26 lks. dist., mkd. X BT on double blaze.

Ascend gentle S. slope.

- 22.90 Coffee Creek, 12 lks. wide, course SW.; continue ascent.
25.65 Same Creek, 12 lks. wide, course S. 25° E.; asc. 80 ft. over S. slope.
33.90 Gravelled road, 20 lks. wide, bears SE. and NW.
39.95 The center W $\frac{1}{16}$ sec. cor. of sec. 7.

From the center S $\frac{1}{16}$ sec. cor. of sec. 7.

N. $89^{\circ} 56'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 7.

Ascend 75 ft. over E. slope.

- 5.70 Wire fence, bears N. 25° E. and S. 25° W.
11.45 Spur, slopes S.; desc. 175 ft. over SW. slope.
18.10 Gravelled road, 20 lks. wide, bears N. 25° E. and S. 25° W.
19.97 True point for the SW $\frac{1}{16}$ sec. cor. of sec. 7, falls in Coffee Creek, 12 lks. wide, course S. 25° E.
From this point the witness corner for the SW $\frac{1}{16}$ sec. cor. of sec. 7 bears N. $0^{\circ} 12'$ W., 37 lks. dist.
Ascend 420 ft. over NE. slope.
42.81 The S $\frac{1}{16}$ sec. cor. of sec. 7 only, on the W. bdy. of the Tp.

From the center W $\frac{1}{16}$ sec. cor. of sec. 7.

N. $0^{\circ} 10'$ W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 7.

Ascend 230 ft. over SW. slope, through moderate timber and undergrowth.

- 17.80 Spur, slopes W.; desc. 40 ft. over broken NW. slope.
27.35 Ravine, drains W.; asc. 35 ft. over SW. slope.
30.25 Spur, slopes W.; desc. 50 ft. over a broken NW. slope.
39.92 The W $\frac{1}{16}$ sec. cor. of secs. 6 and 7.