

County Surveyor's Record, Douglas County, Oregon

14530

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 2 W.

CHAINS

and bearing trees mkd. by Powell

A cedar, 11 ins. diam., bears N. 42° E., 42½ lks. dist., with scribe marks T31S R2W S23 CS BT visible on partially healed double blaze.

A fir, 9 ins. diam., bears S. 81° W., 72½ lks. dist., with scribe marks T31S R2W S22 CS BT visible on partially healed double blaze.

The corner is located at the intersection of fences extending N., E., and W.

N. 0° 17' E., between secs. 22 and 23, marking and blazing the true line.

Descend 100 ft. over broken NW. slope, through cleared area.

15.60 Bottom of descent, slopes W.; asc. 60 ft. over SW. slope.

20.31 Point for the S 1/16 sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

S 1/16
S 22 | S 23
1971

from which

A pine, 23 ins. diam., bears S. 88° E., 104 lks. dist., mkd. S 1/16 S23 BT.

A cedar, 10 ins. diam., bears S. 87° W., 73 lks. dist., mkd. S 1/16 S22 BT.

Ascend 35 ft. over SW. slope.

24.50 Spur, slopes W.; desc. 330 ft. over NW. slope.

40.62 Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

T 31 S R 2 W
 ¼
S 22 | S 23
1971

from which

A fir, 18 ins. diam., bears S. 78° E., 92 lks. dist., mkd. ¼ S23 BT.

A fir, 9 ins. diam., bears N. 44° W., 55 lks. dist., mkd. ¼ S22 BT.

Descend 180 ft. over NW. slope

60.30 Corner of barbed-wire fences, extending N. 85° E. and S. 5° E.

60.93 Point for the N 1/16 sec. cor. of secs. 22 and 23.

Set an iron post, 28 ins. long 2½ ins. diam., 21 ins. in the ground,