

14533 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 2 W.

CHAINS

T 31 S	R 2 W
S 10	S 11
S 15	S 14
1971	

from which new bearing trees

A cedar, 14 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., 50 lks. dist., mkd. T31S R2W S11 BT.

A fir, 8 ins. diam., bears S. 7° E., 57 lks. dist., mkd. T31S R2W S14 BT.

A fir, 7 ins. diam., bears N. 1° W., 74 lks. dist., mkd. T31S R2W S10 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, madrone, cedar, and hemlock; undergrowth, salal, manzanita, willow, poison oak, and vine maple.

N. $0^{\circ} 24'$ E., between secs. 10 and 11.

Descend 70 ft. over NE. slope, through cultivated field.

5.90 Ravine, drains N. 70° E.; asc. 40 ft. over SE. slope.

6.00 Woven wire fence, bears N. 70° E. and S. 70° W.

8.80 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.; enter pasture land, edge bears NE. and SW.

13.50 Spur, slopes E.; desc. 150 ft. over NE. slope.

18.80 Elk Creek, 90 lks. wide, course N. 15° W.; asc. 10 ft. over SE. slope; enter scattering timber and light undergrowth, edge bears N. 15° W. and S. 15° E.

20.22 Point for the S $1/16$ sec. cor. of secs. 10 and 11.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

S $1/16$
S 10 S 11
1971

from which

A black oak 14 ins. diam., bears S. 42° E., 159 lks., dist., mkd. S $1/16$ S11 BT.

A white fir, 13 ins. diam., bears N. 67° W., $29\frac{1}{2}$ lks. dist., mkd. S $1/16$ S10 BT.

Continue over level land.

22.10 Dry creek bed, 7 lks. wide, drains S. 80° W.; asc. 300 ft. over SW. slope.

23.20 State Highway No. 227, paved, 35 lks. wide, bears N. 30° W. and S. 30° E.; enter heavy timber.

40.44 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, re-established in 1928 by H. L. Epstein, County Surveyor, by single proportionment, and remonumented in 1966 by John M. Powell, Deputy County Surveyor, with an iron pipe, 1 in. diam., firmly set, protruding 14 ins.