

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 2 W

CHAINS

above ground, with brass cap mkd.

T 31 S R 2 W
 $\frac{1}{4}$ S 10 | S 11
 1966

from which bearing trees mkd. by Epstein

A fir, 22 ins. diam., bears S. 32° E.; 83 lks. dist., with a healed blaze.

A cedar, 19 ins. diam., bears S. 37° W., 60 lks. dist., with a healed blaze.

Land, mountainous.
 Soil, rocky clay loam.
 Timber, fir, madrone, pine, and cedar; undergrowth, salal, manzanita, willow, poison oak, and vine maple.

From the cor. of secs. 10, 11, 14, and 15.

N. 89° 17' W., between secs. 10 and 15.

Ascend 400 ft. over E. slope; through cultivated field.

- 7.90 Woven wire fence, bears N. 40° E. and S. 40° W.
- 12.50 Gravel road, 15 lks. wide, bears N. 40° E. and S. 40° W.; enter pasture land, edge bears NE. and SW.
- 16.40 Gravel road, 15 lks. wide, bears N. 10° W. and S. 10° E.
- 24.90 Barbed-wire fence, bears N. and S.
- 29.40 Dirt road, 10 lks. wide, bears N. 20° W. and S. 20° E.
- 40.12 The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, remonumented in 1966 by John M. Powell, Deputy County Surveyor, with an iron pipe, 1½ ins. diam., firmly set, protruding 14 ins. above the ground with brass cap mkd.

COUNTY SURVEYORS
 T 31 S R 2 W
 $\frac{1}{4}$ S 10
 S 15
 1966
 OFFICE

from which the original bearing trees;

A white oak, 17 ins. diam., bears N. 31° E., 95 lks. dist., with 30 marks visible.

A white oak, 8 ins. diam., bears S. 79° E., 60 lks. dist., with scribe marks BT visible on partially opened blaze.

and bearing trees mkd. by Powell

A fir, 20 ins. diam., bears S. 18° E., 40 lks. dist., with scribe marks $\frac{1}{4}$ S15 visible on partially opened blaze.

A fir, 23 ins. diam., bears N. 27° W., 13 lks. dist., with scribe marks $\frac{1}{4}$ S visible on pitched over blaze.

The corner falls in a barbed-wire fence, extending N. and S.