

County Surveyor's Record, Douglas County, Oregon

14538

T. 23 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of that portion of township 23 south, range 4 west, pertaining to this resurvey, is as follows:

The mile between sections 13 and 14 was surveyed by Harvey Gordon and Charles T. Gardner, in 1855-56, as shown on the official plat of survey approved February 20, 1956.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines were chained twice. Only those lines bounding, or crossing public lands were blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated March 8, 1971, under Group No. 733, Oregon.

The direction of the line was determined by the solar transit method.

The geographic position of the southwest corner of section 13, T. 23 S., R. 4 W., as scaled from the Anlauf, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 43° 33.8' N. Longitude 123° 07.6' W.

The mean magnetic declination is 18° 15' E.

From the cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1963, at which time evidence of the original NW. bearing tree was in existence, monumented with a 1 in. T iron, firmly set, projecting 8 ins. above the ground

from which bearing trees mkd. by Haines

A fir, 23 ins. diam., bears N. 12° E., 57½ lks. dist., with healed blaze.

A fir, 26 ins. diam., bears S. 21° E., 42½ lks. dist., with healed blaze.

A fir, 21 ins. diam., bears S. 58° W., 95½ lks. dist., with healed blaze.

A fir, 13 ins. diam., bears N. 72½° W., 13 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 23 S R 4 W
S 14 | S 13
S 23 | S 24
1971