

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 8 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

| |
|--------|
| T 23 S |
| R 8 W |
| ¼ S 19 |
| 1969 |

from which new bearing trees

A hemlock, 12 ins. diam., bears N. 77° E., 57 lks. dist., mkd. ¼ S19 BT.

A hemlock, 8 ins. diam., bears N. 41 3/4° E., 57 lks. dist., mkd. X BT.

N. 0° 24' E., along the W. bdy. of sec. 19, marking and blazing the true line.

Ascend 350 ft. over general S. slope, through heavy timber and moderate undergrowth.

8.85 Spur ridge, bears N. 30° E. and S. 30° W.; asc. 115 ft. along W. slope.

18.15 Ravine, drains S. 30° W.; asc. 80 ft. over S. slope.

20.46 Point for the closing cor. of secs. 13 and 24, T. 23 S., R. 9 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| |
|---------------------|
| T 23 S |
| R 9 W |
| CC <u>S 13</u> S 19 |
| S 24 |
| 1969 |

from which

A cedar, 35 ins. diam., bears N. 31½° W., 37 lks. dist., mkd. T23S R9W S13 CC BT.

A fir, 35 ins. diam., bears S. 89° W., 59 lks. dist., mkd. T23S R9W S24 CC BT.

Ascend 185 ft. over S. slope.

27.65 Spur ridge, bears N. 80° E. and S. 80° W.; desc. 375 ft. over N. slope.

36.85 Ravine, drains N. 20° W.; desc. 95 ft. over NW slope.

40.495 Point for the S 1/16 sec. cor. of sec. 13 only, T. 23 S., R. 9 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

| |
|--------|
| S 1/16 |
| S 13 |
| 1969 |

from which