

County Surveyor's Record, Douglas County, Oregon

14544

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 8 W.

CHAINS

A cedar, 10 ins. diam., bears N. 89° W., 77 lks. dist.,
mkd. S1/16 S13 BT.

A hemlock, 10 ins. diam., bears S. 25½° W., 30 lks. dist.,
mkd. S1/16 S13 BT.

40.51 The cor. of secs. 18 and 19 only, perpetuated and recorded by
Vernon Tracy, Deputy County Surveyor, in 1967, monumented with an
iron post, 1 in. diam., firmly set, projecting 8 ins. above ground,
with brass cap mkd.

		SURVEYORS					
COUNTY	R	T 23 S	R			OFFICE	
	9	S 18	8				
	W	S 19 W	W				
		1967					

from which the original bearing trees

A fir, 72 ins. diam., bears N. 15° E., 28 lks. dist.,
with healed blaze.

A cedar, 38 ins. diam., bears S. 75° E., 67 lks. dist.,
with fragmentary scribe marks visible on open blaze.

A cedar, 30 ins. diam., bears N. 79° W., 15 lks. dist.,
no marks visible.

and bearing trees mkd. by Tracey in 1967

A hemlock, 14 ins. diam., bears N. 75° E., 46½ lks. dist.,
with scribe marks T23S R8W S18 CS BT visible on open
blaze.

A hemlock, 8 ins. diam., bears S. 59° E., 40 lks. dist.,
with scribe marks T23S R8W S19 CS BT visible on
open blaze.

N. 0° 11' E., along W. bdy. of sec. 18.

Ascend 95 ft. over SW. slope.

5.00 Spur, slopes N. 55° W.; desc. 145 ft. over NW. slope.

8.65 Ravine, drains W.; asc. 120 ft. over SW. slope.

13.55 Spur, slopes N. 75° W.; desc. 235 ft. over NW. slope.

20.02 Point for the ¼ sec. cor. of sec. 13 only, T. 23 S., R. 9 W.,
at proportionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd.

T 23 S	
R 9 W	
¼ S 13	
1969	