

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 8 W.

CHAINS

from which

A hemlock, 10 ins. diam., bears N. $28\frac{1}{4}^\circ$ W., 47 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

A hemlock, 35 ins. diam., bears S. $93\frac{1}{4}^\circ$ W., 51 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

Descend 245 ft. over NW. slope.

28.40 Creek, 3 lks. wide, course N. 85° W.; asc. 220 ft. over S. slope.

40.03 The $\frac{1}{4}$ sec. cor. of sec. 18 only, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1967, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd

		SURVEYORS		
County	R	T 23 S	R	Office
	9	$\frac{1}{4}$ S 18	8	
	W	1967	W	

from which the remaining original bearing tree

A fir snag, 40 ins. diam., bears S. 5° E., 143 lks. dist., with scribe marks 4S visible on opened blaze.

and bearing trees mkd. by Tracy in 1967

A fir, 11 ins. diam., bears N. 61° E., 56 lks. dist., with scribe marks $\frac{1}{4}$ S18 CS BT visible on open blaze.

A fir, 30 ins. diam., bears S. 47° E., 22 lks. dist., with scribe marks $\frac{1}{4}$ S18 CS BT visible on open blaze.

The corner point is located on top of spur ridge, bears E. and W.

N. $0^\circ 09'$ E., beginning new measurement.

Descend slightly over N. slope.

0.025 Point for the N $\frac{1}{16}$ sec. cor. of sec. 13 only. T. 23 S., R. 9 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $\frac{1}{16}$	
S 13	
	1969

from which

A hemlock, 12 ins. diam., bears N. $89\frac{3}{4}^\circ$ W., 32 lks. dist. mkd. N $\frac{1}{16}$ S13 BT.

A fir, 18 ins. diam., bears S. $17\frac{1}{4}^\circ$ W., 62 lks. dist., mkd. N $\frac{1}{16}$ S13 BT.

Descend 290 ft. over N. slope.

8.70 Creek, 10 lks. wide, course W.; asc. 245 ft. over S. slope.