

14546 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 8 W.

CHAINS

- 10.65 Gravelled road, 15 lks. wide, bears N. 65° W. and S. 65° E.
- 30.65 Spur, slopes NW.; desc. 260 ft. over N. slope.
- 40.31 The cor. of secs. 7 and 18 only, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

		SURVEYORS			
		T 23 S			
COUNTY	R	CC	S 7	R	OFFICE
	9		S 18	8	
	W			W	
1967					

from which the original bearing trees

A fir snag, 30 ins. diam., bears N. 27° E., 88 lks. dist., with scribe marks T23S R8W S7 visible on opened blaze.

A fir, 42 ins. diam., bears N. 57° W., 37 lks. dist., no marks visible.

and bearing trees mkd. by Tracy in 1967

A hemlock, 12 ins. diam., bears N. 36° E., 42 lks. dist., with scribe marks T23S R8W S7 CC CS BT visible on open blaze.

A fir, 15 ins. diam., bears S. 37° E., 14 lks. dist., with scribe marks T23S R8W S18 CC CS BT visible on open blaze.

Land mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, chinquapin, alder, and myrtle; undergrowth, salal, hazel, huckleberry, Oregon Grape, rhododendron, arrowwood, salmonberry and fern.

N. 0° 18' W., along the W. bdy. of sec. 7.

Descend 25 ft. over N. slope.

- 5.40 Paved road, 20 lks. wide, bears N. 55° E. and S. 55° W.
- 8.55 Little Cap Creek, 5 lks. wide, course W.; asc. slightly over SW. slope.
- 9.20 Enter Camp Creek, 20 lks. wide, course N. from S. 20° W.
- 11.30 Leave Camp Creek, course N. 35° W.; asc. 30 ft. over SW. slope.
- 12.10 Same road, bears N. 30° W. and S. 30° E.; also intersection of Lindy Bridge Road.
- 14.52 The cor. of secs. 12 and 13 only, T. 23 S., R. 9 W., determined at record distance from the remains of the original bearing trees;

A sawed fir stump, 36 ins. diam., bears N. 12° E., 45 lks. dist., no marks visible. (Record, N. 15° E.)