

Dependent Resurvey, Portion of W. Bdy., T. 23 S., R. 8 W.

CHAINS

A chinquapin root crown, 20 ins. diam., bears S. 66° E., 36 lks. dist., no marks visible. (Record, S. 52° E.)

and a tree of which I have no record

A fir, 28 ins. diam., bears S. 30° E., 17 lks. dist., with scribe marks T23S R8W S7 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass capmkd.

T 23 S	T 23 S
R 9 W	R 8 W
S 12	S 7
S 13	
1969	

from which new bearing trees and a bearing object

A hemlock, 21 ins. diam., bears S. 81° W., 212 lks. dist. mkd. T23S R9W S13 BT.

A fir, 13 ins. diam., bears N. 13° W., 66½ lks. dist., mkd. T23S R9W S12 BT.

N.E. cor. of Lindy Bridge, bears S. 11¼° W., 252 lks. dist., mkd. with an X chiseled in curb.

The cor. is further substantiated by record calls to Camp Creek, 350 lks. west, and 320 lks. south.

This cor. was established by William H. Byars. in 1878 as the corner to secs. 7, 12, 13 and 18, and became a corner of minimum control during the resurvey of the range line by Williams R. Whipple, in 1894.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, chinquapin, alder, and myrtle; undergrowth, hazel, salal, rhododendron, Oregon Grape, arrowwood and fern.

Dependent Resurvey of a Portion of the South Boundary, T. 22 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the 1878 survey by William H. Byars)

From the cor. of secs. 5, 6, 31, and 32, perpetuated and recorded by the county Surveyor in 1968, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd,

SURVEYORS			
	T 22 S		R
COUNTY	S 31	S 32	OFFICE
	S 6	S 5	
	T 23 S		W
1968			