

County Surveyor's Record, Douglas County, Oregon

14548

Dependent Resurvey, South Boundary, T. 22 S., R. 9 W.

CHAINS

from which the remaining original bearing trees

- A cedar stump, 30 ins. diam., bears N. 60° E., 56 lks. dist., no marks visible, (Record, N. 65° E.)
- A cedar, 60 ins. diam., bears N. 30° W., 105 lks. dist., no marks visible on open blaze.

and bearing trees mkd. by the County Surveyor in 1968

- A hemlock, 30 ins. diam., bears N. 6° E., 28 lks. dist., with scribe marks T22S R9W S32 CS BT visible on open blaze.
- A hemlock, 25 ins. diam., bears S. 45½° E., 38 lks. dist., with scribe marks T23S R9W S5 CS BT visible on open blaze.
- A hemlock 38 ins. diam., bears S. 76° W., 97½ lks. dist., with scribe marks T23S R9W S6 CS BT visible on open blaze.
- A hemlock, 6 ins. diam., bears N. 24° W., 25 lks. dist., with scribe marks T22S R9W S31 CS BT visible on open blaze.

S. 89° 44' W., bet. secs. 6 and 31, marking and blazing the true line.

Ascend 220 ft. over broken NE. slope, through heavy timber and dense undergrowth.

21.05 Top of ascent, slopes NE.; desc. 355 ft. over broken W. slope.

36.00 Creek, 5 lks. wide, course N. 20° W.; asc. 145 ft. over broken E. slope.

39.535 The ¼ sec. cor. of secs. 6 and 31, perpetuated and recorded by the Oregon State Board of Forestry in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

¼ $\frac{S\ 31}{S\ 6}$
1967

from which the original bearing trees

- A fir, 30 ins. diam., bears N. 4° W., 20½ lks. dist., with fragmentary scribe marks visible on open blaze. (Record, North, 18 lks.)
- A fir snag, 30 ins. diam., bears S. 9½° E., 25 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, South, 23 lks.)

S. 89° 22' W., beginning new measurement.

Ascend 25 ft. over W. slope.

1.80 Spur, bears N. 20° W.; desc. 230 ft. over W. slope.

9.70 Creek, 3 lks. wide, course N.; asc. 50 ft. over W. slope.