

# County Surveyor's Record, Douglas County, Oregon

14550

Dependent Resurvey, East Boundary, T. 23 S., R. 10 W.

CHAINS

and bearing trees mkd. by the County Surveyor in 1952

A fir, 23 ins. diam., bears S. 72° W., 32 lks. dist., with fragmentary scribe marks visible on opened blaze.

A fir, 15 ins. diam., bears N. 12 3/4° W., 43 lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 23 S	T 23 S
S 1	R 9 W
S 12	S 7
R 10 W	
1970	

N. 1° 34' W., on the E. bdy. of sec. 1, marking and blazing the true line.

Descend 210 ft. over broken N. slope, through scattering timber and dense undergrowth.

- 7.45 Creek, 1 lk. wide, course N. 85° W.; desc. 45 ft. over broken N. slope.
- 10.90 Creek, 3 lks. wide, course S. 80° W.; asc. 70 ft. over SW. slope.
- 12.75 Spur, slopes W.; desc. 65 ft. over N. slope
- 17.60 Creek, 3 lks. wide, course S. 60° W.; asc. 370 ft. over broken SE. slope.
- 34.80 Ridge, divides Sock Creek drainage and Mill Creek drainage, bears N. 75° E., and S. 75° W.; desc. 55 ft. over NW. slope.
- 36.70 Gravelled road, 20 lks. wide, bears N. 75° E., and S. 75° W.
- 37.31 True point for the closing corner of secs. 6 and 7, T. 23 S., R. 9 W., determined and recorded by the Oregon State Board of Forestry in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, level with the surface of the ground, with brass cap mkd.

T 23 S	T 23 S
S 1	S 6 CC
S 12	S 7
R 10 W	R 9 W
1968	

from which a bearing tree mkd. by the Oregon State Board of Forestry in 1968

A sawed fir stump, 20 ins. diam., bears N. 32° E., 28 lks. dist., with fragmentary scribe marks visible on open blaze.

Descend 15 ft. over broken NW. slope.

- 37.775 Point for the 1/4 sec. cor. of sec. 1 only, at proportionate distance; there is no remaining evidence of the original corner.