

Dependent Resurvey, East Boundary, T. 23 S., R. 10 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., level with the surface of ground, with brass cap mkd.

$\frac{1}{4}$ S 1 |
 T 23 S |
 R 10 W |
 1970

from which

A sawed fir stump, 25 ins. diam., bears S. $0\frac{1}{2}^\circ$ W., 70 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

An alder, 18 ins. diam., bears S. $30\frac{1}{2}^\circ$ W., 30 lks. dist., mkd. X BT.

Raise a mound of stone, 2 ft. base, 2 ft. high, to the W. and deposit broken green glass at base of iron post.

Descend 425 ft. over broken NW. slope.

57.35 Creek, 10 lks. wide, course N. 50° W.; asc. 410 ft. over broken S. slope.

77.10 Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 23 S., R. 9 W., established and recorded by the Oregon State Board of Forestry in 1968, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

| $\frac{1}{4}$ S 6
 1968

from which bearing trees mkd. by the Oregon state Board of Forestry in 1968

A fir, 20 ins. diam., bears S. 81° E., 44 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 30 ins. diam., bears S. $26\frac{1}{4}^\circ$ E., $48\frac{1}{2}$ lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 24 ins. diam., bears N. 61° W., $58\frac{1}{2}$ lks. dist., with fragmentary scribe marks visible on open blaze.

The corner point is located on top of spur ridge, bears NW. and SE.

N. $1^\circ 34'$ W., beginning new measurement.

Descend 175 ft. over NW. slope.

7.45 Creek, 2 lks. wide, course N. 75° E.; desc. 165 ft. over broken NE. slope

21.50 Creek, 2 lks. wide, course N. 50° E.; desc. 315 ft. over broken NE. slope.