

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

- 8.70 Creek, 2 lks. wide, course S. 30° E.; asc. 85 ft. over SW. slope.
- 12.05 Spur, slopes S. 35° E.; desc. 200 ft. over E. slope.
- 19.70 Point for the W 1/16 sec. cor. of secs. 13 and 24.
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground with brass cap mkd.

W 1/16 $\frac{S}{S}$ $\frac{13}{24}$
1969

from which

- A maple, 20 ins. diam., bears N. 11° W., 31½ lks. dist., mkd. W 1/16 S13 BT.
- A hemlock, 18 ins. diam., bears S. 84° W., 55 lks. dist., mkd. W 1/16 S24 BT.

Descend 60 ft. over E. slope.

- 31.90 Camp Creek, 15 lks. wide, course N. 30° E.; asc. 155 ft. over W. slope.
- 33.20 Camp Creek Road, 30 lks. wide, bears N. 15° E. and S. 15° W.
- 39.40 The ¼ sec. cor. of secs. 13 and 24, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

SURVEYORS
T 23 S
COUNTY ¼ $\frac{S}{S}$ $\frac{13}{24}$ OFFICE
R 9 W
1967

from which the original bearing trees

- A fir snag, 30 ins. diam., bears N. 65° E., 26 lks. dist., no marks visible.
- A root hole, bears S. 62½° W., 14 lks. dist., with a down cedar alongside, 20 ins. diam., with scribe marks /4S visible on burned blaze.

and bearing trees mkd. by Tracy, in 1967

- A hemlock, 15 ins. diam., bears N. 23° W., 19½ lks. dist., with scribe marks ¼ S13 CS BT visible on open double blaze.
- A hemlock, 12 ins. diam., bears S. 28° W., 26 lks. dist., with scribe marks ¼ S24 CS BT visible on open double blaze.

And a reference monument established by George C. and Crystal M. Barton in 1966

- An iron pipe, ½ in. diam., bears S. 53° W., 1 lk. dist. with a metal plate, ¼ x 7 x 12 ins., affixed to top, mkd.