

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd.

S 1/16
S 14|S 13
1969

from which

A hemlock, 6 ins. diam., bears S. 32¼° E., 36 lks. dist., mkd. S 1/16 S13 BT.

A fir, 75 ins. diam., bears N. 33° W., 16 lks. dist., mkd. S 1/16 S14 BT.

Ascend 30 ft. over SE. slope.

23.60 Spur, slopes N. 60° E.; desc. 175 ft. over N. slope.

26.80 Wet ravine, drains N. 80° E.; asc. 55 ft. over SE. slope.

29.40 Spur, slopes S. 85° E.; desc. 185 ft. over NE. slope.

34.75 Creek, 4 lks. wide, course S. 70° E. asc. 85 ft. over SE. slope.

39.41 The ¼ sec. cor. of secs. 13 and 14, determined at record bearing and distance from the original bearing trees:

A maple, 23 ins. diam., bears N. 87½° E., 40 lks. dist., with healed blaze.

A fir, 55 ins. diam., bears N. 77° W., 41 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd.

T 23 S R 9 W
¼
S 14|S 13
1969

N. 0° 15' W., beginning new measurement.

Ascend 210 ft. over S. slope.

19.88 Point for the N 1/16 sec. cor. of secs. 13 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd.

N 1/16
S 14|S 13
1969

from which

A hemlock, 11 ins. diam., bears S. 28° E., 21 lks. dist., mkd. N 1/16 S13 BT.

A hemlock 13 ins. diam., bears N. 83½° W., 34½ lks. dist., mkd. N 1/16 S14 BT.

Ascend 85 ft. over S. slope.