

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

S. 89° 32' E., bet. secs. 12 and 13.

Descend 10 ft. over N. slope, along S. edge of timber.

2.40 Ravine, drains N. 35° W.; asc. 215 ft. over NW. slope; also enter timber, edge bears SE. and W.

8.90 Spur, slopes N. 10° W; desc. 70 ft. over NE. slope.

11.85 Head of ravine, drains N.; asc. 45 ft. over NW. slope; enter scattering timber and dense undergrowth, edge bears N. and S.

13.55 Spur slopes N. 20° E.; desc. 225 ft. over E. slope.

14.30 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W., curving to west.

19.515 Point for the W 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam, 24 ins. in ground, with brass cap mkd.

W 1/16  $\frac{S\ 12}{S\ 13}$   
1969

from which

A hemlock, 22 ins. diam., bears N. 50° E., 46 lks. dist., mkd. W 1/16 S12 BT.

A hemlock, 30 ins. diam., bears S. 67° E., 25 lks. dist., mkd. W 1/16 S13 BT.

Descend 220 ft. over SE. slope.

20.05 Enter timber, edge bears N. and S.

29.80 Creek, 5 lks. wide, course N. 35° E.; asc. 60 ft. over NW. slope.

32.00 Spur, slopes N. 15° E.; desc. 95 ft. over NE. slope.

35.10 Creek, 2 lks. wide, course N.; asc. 85 ft. over NW. slope.

39.03 The ¼ sec. cor. of secs 12 and 13, determined at record bearing and distance from the remaining original bearing tree:

A fir, 60 ins. diam., bears N. 50° E., 47 lks. dist., no marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd.

T 23 S R 9 W  
¼  $\frac{S\ 12}{S\ 13}$   
1969

from which

A hemlock, 20 ins. diam., bears N. 51° W., 58½ lks. dist., mkd. ¼ S12 BT.