

# County Surveyor's Record, Douglas County, Oregon

14558

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

A hemlock, 20 ins. diam., bears S. 78° E., 45½ lks.  
dist., mkd. ¼ S13 BT.

S. 89° 28' E., beginning new measurement.

Ascend 35 ft. along N. slope.

5.55 Top of ascent, slopes N.; desc. 305 ft. along general N. slope.

19.47 Point for the E 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground  
with brass cap mkd.

E 1/16    S 12  
          S 13  
          1969

from which

A hemlock, 8 ins. diam., bears N. 84 3/4° W., 20 lks.  
dist., mkd. E 1/16 S12 BT.

A hemlock, 7 ins. diam., bears S. 13 3/4° E., 16½ lks.  
dist., mkd. E.1/16 S13 BT.

Descend 65 ft. along broken N. slope.

35.45 Camp Creek, 30 lks. wide, course N. 80° W., curving to N.;  
asc. 55 ft. over SW. slope.

37.65 Paved road, 30 lks. wide, bears N. 30° W. and S. 30° E.

38.94 The cor. of secs. 12 and 13 only, hereinbefore described.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, alder, cedar, maple, chinquapin, and  
myrtle; undergrowth, salal, hazel, huckleberry, Oregon Grape,  
arrowwood and fern.

From the ¼ sec. cor. of secs. 19 and 20, determined at record  
bearing and distance from a bearing tree marked and recorded  
by Arthur R. Evans, Registered Mining Engineer No. 2741, in 1951.  
Evans determined the corner position by testimony of A. O. Gustafson,  
an interested land owner, who had knowledge of the original corner  
position and bearing trees.

from which Evans bearing tree

An alder, 20 ins. diam., bears N. 50° E., 38 lks.  
dist., with scribe marks ¼ S20 R visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground,  
with brass cap mkd.

T 23 S R 9 W  
          ¼  
          S 19 | S 20  
          1969