

County Surveyor's Record, Douglas County, Oregon

14560

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

Land, mountainous.
 Soil, rocky clay loam.
 Timber, fir, alder, maple, cedar, hemlock, chinquapin, and myrtle; undergrowth, salal, hazel, huckleberry, Oregon Grape, salmonberry, arrowwood and fern.

From the cor. of secs. 16 and 20 only, on the W. bdy. of sec. 21 determined at record bearing and distance from the original bearing trees:

- A sawed fir stump, 27 ins. diam., bears N. 10° E., 33 lks. dist., no marks visible.
- A sawed fir stump, 24 ins. diam., bears S. 88° E., 26 lks. dist., no marks visible.
- A sawed fir stump, 18 ins. diam., bears N. 70° W., 9 lks. dist., with scribe marks BT visible on opened blaze.

and a tree of which I have no record

- A hemlock, 10 ins. diam., bears N. 87½° E., 102 lks. dist., with scribe marks T23S R9W S21 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd.

T 23 S R 9 W
 S 16 | S 21
 S 20 |
 1969

from which new bearing trees

- A hemlock, 9 ins. diam., bears N. 60½° W., 93 lks. dist., mkd. T23S R9W S16 BT.
- A hemlock, 13 ins. diam., bears S. 60° W., 187 lks. dist., mkd. T23S R9W S20 BT.

S. 89° 58' W., along the N. bdy of sec. 20.

Ascend 175 ft. over E. slope, through heavy timber and dense undergrowth.

- 2.80 Gravelled road, 20 lks. wide, bears N. 30° E. and S. 25° W.
- 12.05 Top of ascent, slopes W.; desc. 225 ft. over NW. slope.
- 18.80 Same road, bears N. 55° W. and S. 55° E.
- 31.20 Dry creek, 2 lks. wide, course SW.; asc. 30 ft. over E. slope.
- 32.26 From this point the original closing cor. of secs. 16 and 17, bears North, 11 lks. dist., monumented with a rotted stake, with fragmentary scribe marks visible on N. side, alongside of which is an iron pipe, 1 inch diam., firmly set, protruding 18 ins. above ground, from which original bearing trees: