

County Surveyor's Record, Douglas County, Oregon

14563

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS	
	N. 88° 49' W., beginning new measurement. Descend 130 ft. over SW. slope.
8.15	Ravine, drains S. 10° W.; asc. 30 ft. over SE. slope.
13.20	Spur, slopes SW.; desc. 60 ft. along S. slope.
19.60	Spur, slopes S. 55° W.; desc. 150 ft. over W. slope.
23.80	Creek, 8 lks. wide, course S. 40° W.; asc. slightly over nearly level land.
35.50	Creek, 8 lks. wide, course S. 40° W.; asc. 10 ft. over nearly level open field.
39.89	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.; munumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked and witnessed as described in the official record of the 1967 dependent resurvey. Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, alder, maple, and myrtle; undergrowth, hazel, salal, arrowwood, Oregon Grape, and fern.
	From the cor. of secs. 17, 18, 19 and 20. N. 0° 56' W., bet. secs. 17 and 18. Asc. 10 ft. over broken SE. slope, through scattering timber and moderate undergrowth.
16.05	Creek, 2 lks. wide, course S. 25° E.; asc. 85 ft. over SW. slope.
19.92	Point for the S 1/16 sec. cor. of secs. 17 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd. <div style="text-align: center;">S 1/16 S 18 S 17 1969</div> from which A hemlock, 9 ins. diam., bears N. 52½° E., 60 lks. dist., mkd. S 1/16 S17 BT. A hemlock, 26 ins. diam., bears S. 22½° W., 98 lks. dist., mkd. S 1/16 S18 BT.
	Ascend 250 ft. over SW. slope.
29.60	Spur, slopes E.; desc. 145 ft. over NE. slope.
39.84	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground, with brass cap mkd.