

# 14564 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

T 23 S R 9 W  
 $\frac{1}{4}$   
 S 18 | S 17  
 1969

from which

A hemlock, 20 ins. diam., bears N. 83° E., 47½ lks. dist. mkd.  $\frac{1}{4}$  S17 BT.

A hemlock, 13 ins. diam., bears S. 64 3/4° W., 45 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

Descend 40 ft. over NE. slope.

- 42.00 Ravine, drains N. 55° E.; asc. 30 ft. over SE. slope.  
 44.00 Spur, slopes S. 80° E.; desc. 45 ft. over NE. slope.  
 49.15 Dry creek, course S. 80° E.; asc. 260 ft. over S. slope.  
 57.00 Spur, slopes S. 30° E.; desc. 140 ft. along NE. slope.  
 67.70 Creek, 2 lks. wide, course S. 30° E; asc. 300 ft. over SW. slope.  
 79.68 The cor. of secs. 7 and 18, on the W. bdy. of Sec. 17, monumented with a wooden stake, 3 ins. square, firmly set, projecting 18 ins. above ground, from which the original bearing trees:

A sawed fir stump, 65 ins. diam., bears N. 10° E., 72 lks. dist., no marks visible on bark blaze. (Record, 62 lks.)

A sawed fir stump, 32 ins. diam., bears S. 60° E., 42 lks. dist., no marks visible on open blaze.

A sawed fir stump, 50 ins. diam., bears S. 45° W., 27 lks. dist., no marks visible on bark blaze.

A sawed fir stump, 36 ins. diam., bears N. 60° W., 15 lks. dist., no marks visible on bark blaze.

and a tree of which I have no record

A fir, 12 ins. diam., bears S. 26° E., 13 lks. dist., mkd. T23S R9W S17 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in ground with brass cap mkd.

T 23 S R 9 W  
 $\frac{S 7}{S 18}$  S 17  
 1969

from which new bearing trees

A fir, 10 ins. diam., bears S. 45½° W., 25 lks. dist., mkd. T23S R9W S18 BT.

A fir, 8 ins. diam., bears N. 55° W., 12 lks. dist., mkd. T23S R9W S7 BT.