County Surveyor's Record, Douglas County, Oregon

14566

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 9 W.

CHAINS

From the cor. of secs. 5 and 6 only, on the N. bdy. of sec. 7, perpetuated and recorded by the County Surveyor in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

SURVEYORS
COUNTY T 23 S R 9 W OFFICE
S 6 | S 5
S 7
1967

from which the remaining original bearing trees:

A fir, 75 ins. diam., bears S. 80° W., 138 lks. dist., with healed blaze. (Record, S. 82° W.)

A decayed hemlock stump, 40 ins. diam., bears N. 78° W., 87 lks. dist., with axe marks visible on decayed blaze. (Record, N. 72° W., 84 lks.)

and a tree of which I have no record.

A hemlock, 26 ins. diam., bears S. 75° W., 51½ lks. dist., with fragmentary scribe marks visible on partially open blaze.

and bearing trees mkd. by the County Surveyor in 1967

A hemlock, 20 ins. diam., bears N. 65° E., 64½ lks. dist., with scribe marks T23S R9W S5 BT RS 359 visible on open blaze.

A hemlock, 21 ins. diam., bears N. 55° W., 71 lks. dist., with scribe marks T23S R9W S6 BT RS 359 visible on open blaze.

S. 88° 06' W., on the S. bdy. of sec. 6.

Ascend 50 ft. over broken NE. slope, through heavy timber and dense undergrowth.

6.785 The ¼ sec. cor. of sec. 7 only, perpetuated and recorded by the County Surveyor in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

SURVEYORS
COUNTY ¼ S 7 OFFICE
1967

from which the original bearing trees:

A fir, 90 ins. diam., bears N. 70° W., 49 lks. dist., with healed blaze.

A hemlock, 30 ins. diam., bears S. 63° E., 35 lks. dist., with fragmentary scribe marks visible on partially open blaze.

and a bearing tree mkd. by the County Surveyor in 1967

A fir, 11 ins. diam., bears S. 31° E., 36½ lks. dist., with scribe marks ¼ S7 BT RS 359 visible on open blaze.

S. 89° 56' W., beginning new measurement.