

County Surveyor's Record, Douglas County, Oregon

14567

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R 9 W.

CHAINS

Ascend 65 ft. over broken E. slope, through heavy timber and dense undergrowth.

6.05 Spur ridge, bears N. 5° W., and S. 5° E.; desc. 215 ft. over SW. slope.

13.37 Point for the E. 1/16 sec. cor. of sec. 6 only, established and recorded by the Oregon State Board of Forestry in 1968, monumented with an iron post, 1½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

E 1/16
S 6
1968

from which

A hemlock, 6 ins. diam., bears S. 62° E., 43½ lks. dist., with scribe marks 1/16 S7 BT RS 359 visible on open blaze.

S. 89° 56' W., beginning new measurement.

Descend 25 ft. over W. slope.

1.25 Creek, 2 lks. wide, course N. 35° W.; asc. 240 ft. over broken NE. slope.

15.25 Spur ridge, bears N. 35° W., and S. 35° E.; desc. 70 ft. over SW. slope.

20.125 The ¼ sec. cor. of sec. 6 only, perpetuated and recorded by the Oregon State Board of Forestry in 1967, monumented with an iron post, 1½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

¼ S 6

1967

from which the original bearing trees

A fir, 83 ins. diam., bears N. 4° W., 142 lks. dist., no marks visible on partially open blaze. (Record, N. 2½° W., 134 lks.)

A decayed fir stump, 40 ins. diam., bears S. 54° E., 61 lks. dist., with fragmentary scribe marks visible on partially open blaze. (Record, S. 50° E.)

S. 89° 00' W., beginning new measurement.

Ascend 75 ft. over broken SE. slope.

6.50 Spur ridge, bears N. 75° E., and S. 75° W.; desc. 65 ft. over NW. slope.

8.20 Gravelled road, 20 lks. wide, bears N. 35° E. and S. 35° W.

8.665 The original closing corner of secs. 6 and 7, on the W. bdy. of the Tp., determined at record bearing and distance from the remaining original bearing tree:

A sawed fir stump, 16 ins. diam., bears N. 38½° E., 16 lks. dist., with fragmentary scribe marks visible on partially open blaze.