

# County Surveyor's Record, Douglas County, Oregon

44571

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 1 W.

CHAINS

Beginning at the cor. of secs. 1, 2, 11, and 12, perpetuated by the Douglas County Surveyor, in 1969, with an iron pipe, 1½ ins. diam., firmly set, protruding 14 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 27 S	R 1 W
S 2	S 1
S 11	S 12
1969	

from which the original bearing trees

A fir, 25 ins. diam., bears N. 18° E., 14 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 32 ins. diam., bears S. 46° E., 39 lks. dist., with a healed blaze.

A fir snag, 22 ins. diam., bears S. 14° W., 36 lks. dist., with scribe marks T27S R1W S BT, visible on open blaze. (Record, 37 lks.)

A fir, 25 ins. diam., bears N. 24° W., 42 lks. dist., with partially opened blaze.

and bearing tree marked by the County Surveyor

A fir, 22 ins. diam., bears S. 40° W., 44½ lks. dist., mkd. T27S R1W S11 CS BT.

The original basalt cor. stone, 15 x 8 x 6 ins. is set alongside the iron pipe.

N. 0° 30' E., bet. secs. 1 and 2.

Ascend 100 ft. over gentle S. slope, through heavy timber and light undergrowth.

15.95 Ridge, bears N. 45° E. and S. 45° W.; desc. 320 ft. over NW. slope, through clear cut.

32.90 Gravelled road, 30 lks. wide, bears N. 45° E. and S. 33° W.

33.24 The witness ¼ sec. cor. of secs. 1 and 2, determined from the remains of the original bearing trees:

A hemlock stump, 20 ins. diam., bears N. 75° E., 3 lks. dist., with healed blaze, and buried under 3 ft. of road fill.

A hemlock stump, 26 ins. diam., bears S. 75° W., 23 lks. dist., with scribe marks WC¼ S2 BT visible on opened blaze.

At the original witness corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

Suspension lifted 10/30/1981