

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 27 S R 1 W
 $\frac{1}{4}$
 S 3 | S 2
 1971

No suitable trees within limits

Deposit original stone alongside the iron post.

Land, rolling.

Soil, clay and loam.

Timber, fir, pine and hemlock; undergrowth, willow, rhododendron and marsh grass.

From the cor. of secs. 8, 9, 16 and 17, determined from the remaining original bearing trees:

A hemlock, 26 ins. diam., bears S. 16½° E., 44 lks. dist., with a downed fir, 40 ins. diam., lying in front of the face, (slope dist. to tree is 49 lks. (Record, S. 19½° E., 49 lks.)

A fir snag, 42 ins. diam., bears N. 45° W., 21 lks. dist., mkd. T27S RLW S8 BT, on opened blaze, and metal location tag on tree dated 9/27/43.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 S R 1 W
 S 8 | S 9
 S 17 | S 16
 1971

from which

A fir, 49 ins. diam., bears N. 8° E., 11 lks. dist., mkd. T27S RLW S9 BT.

A fir, 38 ins. diam., bears S. 78° E., 26 lks. dist., mkd. T27S RLW S16 BT.

A fir, 31 ins. diam., bears S. 78° W., 113 lks. dist., mkd. T27S RLW S17 BT.

A hemlock, 12 ins. diam., bears N. 70° W., 162 lks. dist., mkd. T27S RLW. S8 BT.

N. 0° 05' E., bet. secs. 8 and 9.

Ascend 225 ft. over SW. slope, through scattered timber and dense undergrowth.

8.90 Spur, slopes W.; desc. 195 ft. over NW. slope, also edge of timber, enter clear cut, edge bears E. and W.

19.35 Point selected for the witness cor. to the S 1/16 sec. cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Suspension lifted 10/30/1981