

Dependent Resurvey, Portion of Subdivisional Line, T. 27 S., R. 1 W.

CHAINS

22.50 Spur, slopes S. 45° E.; desc. 30 ft. along SW. slope.

24.30 Ravine, drains S.; asc. 280 ft. over SE. slope.

33.90  
39.83 The ¼ sec. cor. of secs. 8 and 17, monumented with a broken basalt stone, 10 x 10 x 5 ins., firmly set, protruding 4 ins. above the ground, no marks visible; from which the remains of the original bearing trees:

A root wad of a maple, size indeterminate, bears N. 63° E., 50 lks. dist., no remains of tree.

A fir snag, 43 ins. diam., bears S. 20° W., 43 lks. dist., with burned and rotted blaze and good axe marks at top and bottom of face, no scribe marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 27 S R 1 W  
¼ S 8  
S 17  
1971

from which

A cedar, 33 ins. diam., bears S. 69° W., 110 lks. dist., mkd. ¼ S17 BT.

A fir, 50 ins. diam., bears N. 9° W., 74 lks. dist., mkd. ¼ S 8 BT.

Deposit the basalt stone alongside iron post

N 89° 23' W., beginning new measurement.

Descend 105 ft. over SW. slope, through scattered timbe and dense undergrowth.

4.85 Ravine, drains S.; asc. 25 ft. over SE. slope.

8.20 Spur, slopes S. 10° E.; desc. 400 ft. over SW. slope.

22.25 Paved road, 30 lks. wide, bears N. 45° W. and S. 45° E.; desc. 10 ft. over SW. slope.

27.10 Little River, 90 lks. wide, 3 ft. deep, course N. 52° W.; asc. 120 ft. over NE. slope, through heavy timber and moderate undergrowth.

33.25 Spur, slopes N. 60° W.; desc. 40 ft. over NW. slope.

40.11 The cor. of secs. 7, 8, 17 and 18, perpetuated by the Douglas County Surveyor, in 1969, with an iron pipe, 1½ ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 27 S R 1 W  
S 7 | S 8  
S 18 | S 17  
1969

Suspension lifted 10/30/1981