

County Surveyor's Record, Douglas County, Oregon

11580

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 1 W.

CHAINS	
	<p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 51 ins. diam., bears N. 23° E., 47 lks. dist., no marks visible on rotted blaze.</p> <p>and bearing trees marked by the County Surveyor</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 2° E., 33 lks. dist., with scribe marks T27S RLW S8 CS BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 50° E., 142 lks. dist., with scribe marks T27S RLW S17 CS BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears West, 17 lks. dist., with scribe marks T27S RLW S18 CS BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 16° W., 30 lks. dist., with scribe marks T27S RLW S7 CS BT visible on partially healed blaze.</p> <p>Land, mountainous. Soil, clay and loam. Timber, fir, pine, cedar and hemlock; undergrowth, vine maple, salal, huckleberry and rhododendron.</p>
	<p>N. 0° 11' E., bet. secs. 7 and 8.</p> <p>Descend 60 ft. over NW. slope.</p>
1.35	<p>Little River, 60 lks. wide, 4½ ft. deep, course S. 60° W.; asc. 575 ft. over S. slope, through heavy fir reproduction and dense undergrowth.</p>
6.20	<p>Paved road, 30 lks. wide, bears N. 89° E. and S. 80° W.</p>
19.855	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in amount of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 7 S 8 1971</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 24° E., 35 lks. dist., mkd. S1/16 S8 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 77½° W., 16 lks. dist., mkd. S1/16 S7 BT.</p> <p>Ascend 325 ft. over S. slope.</p>
23.28	<p>Dirt road, 14 lks. wide, bears N. 65° W. and S. 75° E.; slope changes to SW.</p>
39.71	<p>The ¼ Sec. cor. of secs. 7 and 8, monumented with the original basalt stone, 36 x 20 x 12 ins., firmly set, 30 ins. in the ground, mkd. ¼ on W. face, from which the remaining original bearing tree;</p>

Suspension lifted 10/30/1978