

County Surveyor's Record, Douglas County, Oregon

11582

T. 29 S., R. 1 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 29 south, range 1 west, Willamette Meridian, Oregon, pertaining to this resurvey is as follows:

A portion of the south boundary of township 29 south, range 1 west, was surveyed by Dennis Hathorn in 1857, as shown on the official plat of survey, approved February 20, 1858.

A portion of the south boundary, township 29 south, range 1 west, was retraced and a portion of the south and west boundaries surveyed by Fred Mensch in 1905 and amended in 1907, as shown on the official plat of survey, approved June 29, 1906.

A portion of the west boundary of township 29 south, range 1 west, was resurveyed by Elmer F. Strickler in 1917, as shown on the official plat of survey, approved June 10, 1918.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines were measured twice.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 29, 1971, for Group No. 748, Oregon.

method.

The directions of the lines were determined by the solar transit method.

The geographic position of the corner of sections 5, 6, 31, and 32, on the south boundary of the townships, as scaled from the Red Butte, Oregon quadrangle map, prepared by the United States Geological Survey in 1955, is as follows:

Latitude: 43° 00.2' N. Longitude: 122° 51.7' W.

The mean magnetic declination is 20° East.

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 1 W., Willamette Meridian, Oregon

(Restoring the 1857 survey by Dennis Hathorn and the 1905-1907 survey and resurvey by Fred Mensch)

Beginning at the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., remonumented by F. Mensch in 1905, perpetuated and recorded by John H. Markham, Registered Engineer, in 1960, and subsequently perpetuated and recorded by J. A. Hoffbuhr, Registered Land Surveyor No. 222, in 1970, with an iron pipe, 2½ ins. diam., firmly set, protruding 10 ins. above ground, in amount of stone, 1½ ft. base, to top, with brass cap mkd.

T 29 S	R 1 W
S 31	S 32
S 6	S 5
T 30 S	R 1 W
ELS 222	