

# County Surveyor's Record, Douglas County, Oregon

1:581

Dependent Resurvey, Portion of S. Ely., T. 29 S., R. 1 W.

CHAINS

from which the remaining original bearing tree

A fir stump, 30 ins. diam., bears N. 70° W., 33 lks. dist., mkd. with rotted face.

and bearing trees mkd. by J. H. Markham

A fir, 10 ins. diam., bears N. 2° E., 26 lks. dist., mkd. with healed blaze.

An alder, 14 ins. diam., bears S. 65° E., 11 lks. dist., with scribe marks  $\frac{1}{4}$  S6 visible on partle healed blaze.

A pine, 22 ins. diam., bears S. 15½° W., 14 lks. dist., mkd. with healed blaze.

A fir, 16 ins. diam., bears N. 76° W., 29 lks. dist., mkd. with healed blaze.

A careful search was made for the  $\frac{1}{4}$  sec. cor. established by F. Mensch. No evidence was found.

Cor. falls in a dense stand of timber and scattering undergrowth.

---

N. 89° 56' W., beginning new measurement.

Ascend 230 ft. over gentle E. slope.

2.40 Dirt road, 15 lks. wide, bears N. and S. 6° E. on curve.

20.80 Point for the W 1/16 sec. cor. of sec. 31 only, at proportionate distance.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 S 31  
1971

from which

A yew, 11 ins. diam., bears N. 15 ¾° E., 32 lks. dist. mkd. W 1/16 S31 BT.

A fir, 15 ins. diam., bears N. 71° W., 102 lks. dist., mkd. W. 1/16 S31 B.T.

Ascend 117 ft. over E. slope.

28.60 Ridge, bears N. 23° E. and S. 8° E.; desc. 154 ft. over W. slope; enter old growth, timber, edge bears N. and S.

40.56 The cor. of secs. 1, 6, 31, and 36, remonumented by Fred Mensch in 1905, subsequently remonumented by Elmer F. Strickler in 1917, with an iron pipe, 3 ins. diam., firmly set, extending 14 ins. above ground, with brass cap mkd.

T 29 S  
R 2 W R 1 W  
S 36 | S 31  
S 1 | S 6  
R 2 W R 1 W  
T 30 S  
1971