

County Surveyor's Record, Douglas County, Oregon

14585

Dependent Resurvey, Portion of S. Bdy., T. 29 S., R. 1 W.

CHAINS

from which the remaining original bearing trees, recovered and reblazed by F. Mensch

An oak snag, 21 ins. diam., bears N. 6° E., 75 lks. dist., mkd. with rotted blaze. (Record, N. 2° E., 83 lks.)

An oak snag, 28 ins. diam., bears N. 71° W., 57 lks. dist., mkd. with rotted blaze. (Record, N. 73° W.)

and bearing trees mkd. by F. Mensch

A fir, 17 ins. diam., bears S. 09° E., 19 lks. dist., with illegible scribe marks visible on partly healed blaze. (Record, S. 12° E., 20 lks.)

A fir, 10 ins. diam., bears S. 39° W., 51 lks. dist., with illegible scribe marks visible on partly healed blaze.

and bearing trees mkd. by J. Powell in 1967

A fir, 17 ins. diam., bears N. 72½° E., 25 lks. dist., with illegible scribe marks visible on partly healed blaze.

A fir, 16 ins. diam., bears N. 46° W., 41 lks. dist., with illegible scribe marks visible on partly healed blaze.

Land, steep rolling hills.

Soil, rocky sandy loam.

Timber, pine, fir, alder, cedar, oak, madrone, and chinkapin; undergrowth, hazel brush, arrow wood, and manzanita.

Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 1 W., Willamette Meridian, Oregon

(Restoring the 1905-07 survey by Fred Mensch and the 1917 survey and resurvey by Elmer F. Strickler)

From the cor. of secs. 1, 6, 31, and 36.

N. 0° 30' E., bet. secs. 31 and 36.

Ascend 6 ft. over nearly level W. slope, through dense timber and light undergrowth.

4.00 Top of ascent, slopes W.; desc. 248 ft. over SW. slope.

19.20 Dry creek, 4 lks. wide, drains N. 86° W.; asc. 356 ft. over NW. slope.

30.40 Johnnie Springs Road, dirt, 15 lks. wide, bears N. 51° W. and S. 37° E. on curve.

39.73 The ¼ sec. cor. of sec. 31 only, perpetuated by John M. Powell, County Surveyor, in 1969, with an iron post, 1 in. diam., firmly set, flush with the ground, with brass cap mkd.

T	29	S	
R	1	R	
2	S	31	1
W			W
1969			